



◀ Wirewound Potentiometer ▶

APPLICATION 應用

1. Bushings mount for angle control of the situation requires.
軸套安裝型，適用於需要角度控制的場合。
2. 320° continuous rotation, the effective angle of 320° (can be customized)
320° 連續旋轉，有效角度320°（可定制）
3. Aluminum alloy case, sealed, can be applied in harsh environments.
硬塑料外殼，全密封，可在惡劣環境下適用。

SPECIFICATIONS 規格

Resistance電阻阻值	1K, 5K, 10K
Resistance deviation阻值偏差	±5%
Independent Linearity獨立線性	±0.5%
Electrical angle電氣轉角	320°
Mechanical angle機械轉角	320° continuous
Insulation Resistance絕緣電阻	>500DC. 500V/m
Rated Power額定功率	1W/70°C
Resolution分辨率	Infinte
Smoothness平滑性	≤1.5%
Temperature coefficient溫度係數	±50PPM/°C
Strength耐壓強度	500V. A. C. /min
Starting torque啟動力矩	<0.098 N(M)
Temperature range溫度範圍	-40°C ~ +125°C
Rotary Life回轉壽命	30×10 ⁴ cycles
Protection class防護等級	IP64

ORDERING INFORMATION 訂購說明

PR22B-	Resistance 電阻阻值	Angle 電氣/機械角度	Shaft length 軸柄長度	Shaft type 軸柄形式	Shaft diameter 軸柄直徑	Linearity 線性精度
	1K 5K 10K	320° /320°	20:20mm	S:  F: 	6:ø6mm	Blank: ±0.5%