



ELECTRICAL SPEC.

Detection System	Incremental 增量型
Output Wave 輸出波形	Square Wave 方波
Standard Number of Pulse Per Revolution 解析	5, 10, 20, 30, 40, 50, 60, 80, 100, 120, 150, 180, 200, 250, 300, 360, 400, 500, 600, 720, 800, 900, 1000, 1024, *1800, 2000, *2048, 2500, *3000, *3600, *4000, *4096, *5000 * only with AB phase
Output Phase 輸出相	AB phase or ABZ phase
Electronics 電路特性	NPN Voltage, NPN Open Collector, Push Pull or Line Driver
Power Supply 供應電源	DC 8~26V, DC 5V fixed
Current Consumption 消耗電流	≤ 60 mA
Output Capacity 輸出容量	Sync. Current: 20 mA, Residual Voltage: 0.5V or less
Max. Response 最大響應頻率	10K Hz ~ 100K Hz
Phase Different 相位差	A, B phase different 90°±45° (T/4±T/8), Z phase T±T/2
Wave Form Rise / Fall 波形上下時間	2 μs or less
Polarity 極性保護	Against Reverse Protection (not with DC 5V)

MECHANICAL SPEC.

Shaft Diameter 軸徑	8 mm
Shaft Loading 軸荷重	(10 ~ 1000 PPR) Axial: 4 Kg, Radial: 8 Kg (over 1000 PPR) Axial: 2 Kg, Radial: 4 Kg
Starting Torque (at 25°C) 起動轉矩	260 gf-cm or less
Max. Speed 最大機械容許速度	6,000 rpm
Vibration 震動	10g (10±1,500 Hz)
Shock 衝擊	20g per 11 ms
Cable 電線	Ø5.4, 100 cm long
Weight 重量	≤ 420g

ENVIRONMENTAL SPEC.

Operating Temp. / Humidity 操作溫度/濕度	-10°C ~ 60°C, RH 35% ~ 90% (No Condensation)
Storage Temp. 儲存溫度	-20°C ~ 80°C
Protection 保護等級	IP 64: dust & dripping proof

ORDERING INFORMATION

HSK	-	<div style="border: 1px solid black; padding: 2px;"> <i>Pulse per Revolution</i> 解析 </div>	-	<div style="border: 1px solid black; padding: 2px;"> <i>Output Phase</i> 輸出相 </div>	-	<div style="border: 1px solid black; padding: 2px;"> <i>Electronics</i> 電路特性 </div>	-	<div style="border: 1px solid black; padding: 2px;"> <i>Supply Voltage</i> 供應電源 </div>	-	<div style="border: 1px solid black; padding: 2px;"> <i>Connection</i> 出線方式 </div>
		5, 10, 20, 30, 40, 50, 60, 80, 100, 120, 150, 180, 200, 250, 300, 360, 400, 500, 600, 720, 800, 900, 1000, 1024, *1800, 2000, *2048, 2500, *3000, *3600, *4000, *4096, *5000 P/R *only with AB phase		2: AB phase 3: ABZ phase 4: AB+Z high phase		Blank: NPN Voltage C: NPN Open-Collector PP: Push-Pull *L: Line Driver 5Vdc *HL: Line Driver 5~26Vdc		Blank: 8~26Vdc 5V: 5Vdc fixed		Blank: Axial Cable *R7: Radial 7 pin *R10: Radial 10 pin